

SUBSTITUTE SPECIFICATION
(CLEAN VERSION)

Filed: 11-26-2003

METHOD FOR PRODUCING AN INTEGRATED CIRCUIT WITH A
REWIRING DEVICE AND CORRESPONDING INTEGRATED CIRCUIT

5

CLAIM FOR PRIORITY

This application claims priority to German Application No. 10255844.2 filed November 29, 2002, which is incorporated herein, in its entirety, by reference.

10

TECHNICAL FIELD OF THE INVENTION

The present invention relates to a method for producing an integrated circuit with a rewiring device, and a corresponding integrated circuit.

15

BACKGROUND OF THE INVENTION

CSPs (chip scale packages) have to date predominantly been constructed on prefabricated substrate strips. In accordance with known CSP technologies based on a substrate, such as Tessera μ BGA (micro ball grid array), for example, the rewiring (redistribution lines) or at least parts thereof are already integrated into the prefabricated substrate. Such a rewiring present on the substrate is then contact-connected by means of bonding wires or TAB bonding to an integrated circuit or a chip. The production of the substrate requires complicated and expensive process steps which increase the costs for the substrate. Furthermore, the production and the subsequent process steps are effected with a low degree of parallelism, e.g. in panels or strips with fewer than 150 chips. Both causes have hitherto prevented a further lowering of the production costs of CSPs. Fan-out rewirings can also be generated by means of CSP technologies based on a substrate, for example by means of the BGA technology.

O.K.
to

Enter

L.W.L.

2-9-2006